

PA-M4RC

Order no.: 0179310

PRODUCT INFORMATION

PA zone paging microphone,
for PA matrix mixing amplifier PA-M224 or PA-M412.

- 4 zone selector switch
- ALL-CALL button
- Plug-in electret gooseneck microphone (3-pole XLR jack)
- Phantom power for gooseneck microphone
- LED indication for signal status
- Power supply via PA-M224 or PA-M412
- Connection to PA-M224 or PA-M412 via RJ45 jack and Cat. 5e network cable (copper, supplied w/o cable), cable length up to 200 m

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety and warning notices

Only use the device indoors and protect it from dripping and splashing water, high humidity and heat (permissible operating temperature range 0 - 40 °C).
Do not operate the appliance if there is visible damage to the appliance, if a defect is suspected after a fall or similar, or if malfunctions occur. Always return the appliance to a specialised workshop for repair.
If the appliance is to be taken out of service permanently, hand it over to a local recycling centre for environmentally friendly disposal.

SPECIFICATIONS

PA-M4RC

Description	PA zone paging microphone
Transmission method	cable
System	electret
Power supply	via PA-M224, PA-M412
Audio frequency range	45-15,000 Hz
Sensitivity	1 mV/Pa
Gooseneck length	420 mm
Admiss. ambient temp.	0-40 °C
Dimensions	140 x 65 x 205 mm
Weight	860 g
Connection	RJ45
Packaging dimensions (W x H x L)	0.1 x 0.21 x 0.35 m
Gross weight	1.09 kg
Net weight	0.86 kg

PA-M4RC

EAN code	4007754273397
Net weight	0.86 kg