PUBLIC ADDRESS / SPEAKERS / SOUND PROJECTORS

PF-24T

UNIDIRECTIONAL SOUND PROJECTOR



IP55

- Excellent sound quality
- Excellent finish and elegant design
- IP-55 protection

+ Info:
https://fonestar.com/PF-24T

ESPECIALLY RECOMMENDED IN:


Factories


Education


Transport Stations


All sectors

DESCRIPTION

5" double cone sound projector. 10/5/2.5 W RMS@100 V. IP-55 protection. Adjustable fixing mount.

TECHNICAL CHARACTERISTICS

FEATURES	Sound projector with 100 V line transformer.
POWER	15 W maximum, 10 W RMS
LOUDSPEAKERS	5" double cone, varnished cardboard and mylar
RESPONSE	150-15,000 Hz
IMPEDANCE	10 W RMS@100V (1,000 Ohm) 5 W RMS@100V (2,000 Ohm) 2.5 W RMS@100V (4,000 Ohm)
SENSITIVITY	89 dB at 1 W/1 m
MAXIMUN SOUND PRESSURE	99 dB to max. W/1m
DISPERSION	130°@1kHz, 100°@2kHz, 50°@4kHz (-6 dB)
PROTECTION	IP55 in compliance with 60529
MATERIAL	ABS high resistance to sun exposure Hermetic casing. Aluminium grille Aluminium mount Stainless steel screws A2
TEMPERATURE RANGE	-25°C ~ 55°C
COLOUR	White (RAL 9016)
DIMENSIONS	138 mm Ø x 205 mm depth
WEIGHT	1.6 kg
ACCESSORIES	Adjustable fixing mount


+ Info:
https://fonestar.com/PF-24T