PUBLIC ADDRESS / SPEAKERS / SOUND COLUMNS

TOWER-20TB

100 V LINE TRANSFORMER SOUND COLUMN



IP44

- Optimized for voice
- Great directivity, avoids coupling and reverberation
- Concentration of sound in the audience area
- IP-44 protection

+ Info:
https://fonestar.com/TOWER-20TB

ESPECIALLY RECOMMENDED IN:



All sectors

DESCRIPTION

4 x 2 ½'' sound column. 20/10 W RMS@100 V. IP-44 protection. Fixing mounts.

TECHNICAL CHARACTERISTICS

FEATURES	Sound column with 100V line transformer
POWER SUPPLY	30 W maximum, 20 W RMS
SPEAKERS	4 x 2 ½" speakers
RESPONSE	170-15,000 Hz
IMPEDANCE	20 W RMS@100 V (500 Ohm) 10 W RMS@100 V (1.000 Ohm)
SENSITIVITY	91 dB at 1 W/1 m
DISPERSION	170° H x 95° V (1 kHz) 150° H x 75° V (4 kHz)
PROTECTION	IP-44
MATERIAL	Aluminium enclosure Aluminium mesh
COLOUR	White (RAL 9016)
DIMENSIONS	10.6 x 40.5 x 7.5 cm depth
WEIGHT	2 kg
ACCESSORIES	Fixing mounts



+ Info:
https://fonestar.com/TOWER-20TB